

WHAT IS CLAIMED IS:

1. A method of heat-treatment of a package, comprising the steps of:
placing a number of packages in a retort,
5 pressurising the retort to a first pressure by the supply of a gaseous
pressurisation medium with low moisture content, such as air or the like,
supplying a heating medium for heating the package and the product packed in
the package,
raising, in connection with the supply of the heating medium, the pressure in
10 the retort to a second pressure, and
reducing, during the final phase of the heat-treatment, the pressure in the retort
in such a manner that the pressure of the product packed in the package is higher than
or equal to the pressure prevailing in the retort outside the package.
- 15 2. The method as claimed in Claim 1, wherein said first pressure is at least
approximately 1 bar, preferably approximately 2 bar, or more preferably 3 bar.
- 20 3. The method as claimed in Claim 1, wherein said first pressure is
approximately the same as said second pressure.
- 25 4. The method as claimed in any of the preceding Claims, wherein said second
pressure is of the order of magnitude of 3 to 6 bar, preferably approximately 4 to 5
bar.
- 30 5. The method as claimed in any of the preceding Claims, wherein said
heating medium is steam.
6. The method as claimed in Claim 5, further comprising the step of supplying
water via a number of nozzles to the outside of the packages.
7. The method as claimed in any of the preceding Claims, comprising the step
of selecting, as package, a package of a paper-based packaging laminate.